



FBL4000 PRO

WALK THROUGH METAL DETECTOR



Finger



RFID



Access Control

WALK THROUGH METAL DETECTOR

PARAMETERS

Power Requirements	AC 100 ~ 120V/200 ~ 240V, 50/60Hz
Working Temperature	-28°C to 60°C
Working Humidity	5%RH to 80%RH
Speed of Throughput	RFID: Maximum 30/minute Fingerprint: Maximum 25/minute
Lane Width (mm)	600 (mm)
Footprint (mm*mm)	1350 * 1200
Dimension (L*W*H)	1350*300*1010 (mm)
Dimension with	1500*840*1100 (mm)
Packing (L*W*H)	
Weight with Packing (kg)	169kg
Net Weight (kg)	116kg
LED Indicator	Supports
Control System	SUS304 Stainless Steel

FBL4000 PRO WALK THROUGH METAL DETECTOR

PARAMETERS

Lid Material	SUS304 Stainless Steel
Barrier Material	Acrylic
Barrier Movement	Retracting
Emergency Mode	Supports
Security Level	Medium
MCBF	2 million

Software
Desktop, Web, Cloud



Access Control



Employee Self Service



Mobile App

Disclaimer : Product specifications are given here is for information purpose only and it may change at any time WITHOUT prior notice. We request our customers that before purchase, confirm with us about available features

NEXA SOLUTIONS

Sales : +974 4145 9393

WhatsApp : +974 7139 4477

Support : support@nexasolutions.com.qa

Sales : sales@nexasolutions.com.qa

Website : <https://www.nexasolutions.com.qa>

Address : Hleyton Tower Building No 98, Street 920,
Zone 18 Floor 7, Office No 33, Doha, Qatar